

FIRE RETARDANT "THERMAL BARRIER COATING"

FLAME SEAL TB™

SAFETY DATA SHEET

	SECTION 1 PRODUCT & COMPANY INFORMATION		
1.1	Product Identifier		
	Product Name	FLAME SEAL TB™ "THERMAL BARRIER COATING"	
	Brand	Flame Seal Products, Inc.	
	CAS#	NA	
1.2	Relevant identified uses of the substance or mixt	ture and uses advised against	
	Identified uses	Intumescent fire retardant coating.	
1.3	Details of the Supplier of the Safety Data Sheet		
	Company	Flame Seal Products, Inc.	
		15200 West Drive	
		Houston, TX 77053 USA	
	Telephone	713-668-4291	
	Fax	713-668-1724	
1.4	Emergency telephone number		
	Emergency #	800-424-9300	

CHARLANIA	
SECTION 2	HAZARDS IDENTIFICATION

2 1	Classification of the substance or mixture	

GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Eye irritant (2B), Skin irritant (3)

2.2 GHS Label Elements, including precautionary statements

	Hazard Statements WARNING	
H316:3 Causes mild skin irritation.		Causes mild skin irritation.
	H320 : 2B	Causes eye irritation.
	Precautionary Statements	
	P202	Do not handle until all safety precautions have been read and understood.
	P264	Wash skin thoroughly if exposed.
	P280	Wear eye/face protection.
	P281	Use personal protection equipment as required.
	P305 + P351 + P338	In case of eye contact: rinse thoroughly with eyelid(s) held open. Remove contact lenses, if worn.
	P332 + 313	If skin irritation occurs: get medical advice/attention.
	P337 + P313	If eye irritation persists: get medical advice/attention.
2.3	Other Hazards	

May be harmful if swallowed.

For the full text of the H-Statements mentioned in this section, see Section 16.

SDS v1.1 | Date: 02/09/2016



	SECTION 3	COMPOSITION/INFO	RMATION ON INGREDII	ENTS	
3.1	Substances				
	Formula		*Proprietary aminic phosphate	polymer in water	52 +/- 5%
			*Proprietary performance addi	itives (non hazardous)	14 +/- 5%
			Titanium Dioxide	CAS # 13463-67-7	2 +/- 1%
			Water	CAS # 7732-18-5	32 +/- 5%
	Hazardous Compoi	nents	CAS#	Classification	Concentration
	aminic phosphate pol	ymer		eye (2B), mild skin irritant (3)	52 +/- 5%
	Titanium Dioxide		13463-67-7	See section 11	2 +/- 1%

^{*} Components are a Company Trade Secret – Business Confidential. Flame Seal Products Inc. is withholding the specific chemical identity under provision of the OSHA Hazard Communication Rule Trade Secrets (1910.1200(i)(1). The specific chemical identity will be made available to health professionals in accordance with 29 CFR 1910.1200(i)(1)(2)(3)(4).

	SECTION 4 FIRST AID MEASURES				
4.1	Description of first aid measures				
	General advice	Use good industrial hygiene procedures.			
	If inhaled	Not expected to be an issue in low quantities. Wear respirator rated for organic mist in if adequate ventilation is not available.			
	In case of skin contact	Wash with soap and plenty of water. If irritation occurs, get medical advice/attention.			
	In case of eye contact	Flush eyes with plenty of fresh water while holding eyelids open. Remove contact lenses if worn. If eye irritation persists, get			
		medical advice/attention.			
	If swallowed	Do not induce vomiting. Never give anything by mouth to an unconscious person. Flush mouth with water. If conscious give			
		water to further dilute chemical. Consult physician.			
4.2	Most important symptoms and effects,	The most important known symptoms and effects are described in the labelling (see section 2.2) or in Section 11.			
	both acute and delayed				
4.3	Indication of any immediate medical attention	No data available			
	and special treatment needed				

	SECTION 5 FIRE FIGHTING ME	ASURES
5.1	Extinguishing media	Not combustible (use water spray, fog, foam, dry chemicals, CO ₂ or other agents as appropriate for material in surrounding fire).
5.2 Special hazards arising from substance Heating and/or burning may l		Heating and/or burning may liberate small amounts of ammonia, oxides of nitrogen and phosphorus.
	or mixture	
5.3	Advice for firefighters Not combustible (use safety equipment which is suitable for materials in surrounding fire).	
5.4	Further information No data available	

	SECTION 6 ACCIDENTAL RELEA	ASE MEASURES
6.1	Personal precautions, protective equipment	Use personal protective equipment. Avoid breathing mist. Ensure adequate ventilation. Evacuate personnel from affected area.
	and emergency procedures	For personal protection, see Section 8.
6.2	5.2 Environmental precautions Prevent further leakage or spillage, if safe to do so. Keep out of public sewers and waterways.	
6.3	Methods and materials for containment	Confine spilled material and absorb with sand, sawdust, earth or other available solids. Sweep up and place in a suitable
	and cleaning up.	container for disposal.
6.4	Reference to other sections	See Section 13 for further disposal info.

Flame Seal Products, Inc. 15200 West Drive, Houston, TX 77053 USA

FIRST AIR MEASURES

www.flameseal.com | 713-668-4291 (office) | 713-668-1724 (fax) | **Emergency No. (Chemtrec): 800-424-9300**

SDS v1.1 | Date: 02/09/2016



	SECTION 7 HANDLING & STORA	GE
7.1 Precautions for safe handling Wear appropriate protective equipment. Provide adequate ventilation. See Sections 2.2 and 8.		
7.2 Conditions for safe storage, Keep con		Keep container tightly sealed when not in use. Use good industrial practices to avoid spills.
including any incompatibles		
7.3	7.3 Specified end use ICC certified fire protective coating for tested spray-applied polyurethane foamed plastic.	

	SECTION 8 EXPOSURE CONTR	ROL/PERSONAL PROTECT	TION		
B.1	Control Parameters				
	Components with workplace control parameters	S:		ACGIH	OSHA
	Titanium Dioxide (respirable form)	CAS # 13463-67-7	EC#236-675-5	10mg/m³ TLV-TWA	15 mg/m ³
				respirable fraction 1 mg/m ³	Total dust 8 hr TWA
	Engineering Controls	Handle in accordance with goo	od industrial and safety pra	ctices. Wash hands after handling.	
	Personal Protection Equipment	Respiratory Protection	For heavy mist exposure	e, use a NIOSH/MSHA approved respi	irator suitable for use with
		(Specify Type)	organic vapors if proper	ventilation cannot be provided.	
		Remediation or sanding	Contains titanium dioxid	le which is considered a potential hum	nan carcinogen in respirable
			form. Do not breath dust	t. Use measures to control dust to publ	ished exposure level limits.
			Otherwise wear NIOSH	suitable respirator for hazardous dust	- N100, P100, R100 filters.
		Protective Gloves	Wear impervious gloves	as necessary to avoid excessive skin of	contact (i.e. rubber or neoprene)
		Eye Protection	Protective glasses or gog	ggles in heavy mist areas.	
		Other Protective	Adequate clothing to min	nimize direct contact with skin.	
		Equipment			
	Ventilation	Local Exhaust	Use exhaust fans if neces	ssary to control mist or vapor.	
		Mechanical (general)	Normal room ventilation	1.	
		Special	NA		

	SECT	10N 9 PHYSICAL PROP	PERTIES AND CHEMICAL PR	OPER	TIES	
_	7.1 Information on Basic Physical & Chemical Properties					
	a)	Appearance	White liquid	k)	Vapor pressure	No data available
	b)	Odor	None	l)	Vapor density	No data available
	c)	Odor threshold	NA	m)	Relative density	1.36 - 1.41
	d)	pH	2.0 - 3.0	n)	Water solubility	Completely soluble
	e)	Melting/freezing point	NA/~30 °F	0)	Partition coefficient n-octanol/water	No data available
	f)	Initial boiling point	~212 °F	p)	Auto ignition temp	None
	g)	Flash point	None to boiling	q)	Decomposition temp	No data available
	h)	Evaporation rate	No data available	r)	Viscosity	500 - 650 cP Brookfield
	i)	Flammability	None	s)	Explosive properties	No data available
	j)	Upper/lower flamm limits	No data available	t)	Oxidizing properties	No data available

SECTION 10 STABILITY & REACTIV		VITY
10.1	Reactivity	No data available
10.2	Chemical Stability	Stable under recommended storage conditions
10.3	Possibility of hazardous reactions	None known
10.4	Conditions to avoid	Evaporation – Keep container sealed tightly when not in use
10.5	Incompatible materials	Strong bases and alkalis
10.6	Hazardous decomposition products	Phosphorous nitrogen oxides

Flame Seal Products, Inc. 15200 West Drive, Houston, TX 77053 USA

www.flameseal.com | 713-668-4291 [office] | 713-668-1724 [fax] | **Emergency No. (Chemtrec): 800-424-9300**

SDS v1.0 | Date : 05/29/2015



Information on toxicological effects	
Acute toxicity	LD50 Oral (rat) > 2000 mg/kg
	LD50 Dermal (rat) > 5000 mg/kg
	Conclusions drawn from relevant literature and documentation from similar products.
Inhalation	Not established. Not expected to be harmful. If necessary, use respirator if adequate ventilation is not possible to keep exposu-
	to particulate matter at a minimum in heavy mist areas when spraying.
Dermal	May be irritating with continual contact.
Skin corrosion/irritation	No available data
Serious eye damage/eye irritation	May cause moderate eye irritation if exposed.
Respiratory or skin sensitization	Prolonged exposure may cause skin reddening.
Germ cell mutagenicity	No data available
Carcinogenicity	Titanium Dioxide – Respirable form
IARC	Group 2B: Possibly carcinogenic to humans.
	(a) Although IARC has classified titanium dioxide as a possible carcinogenic to humans (2B), their summary concludes:
	"No significant exposure to titanium dioxide is thought to occur during the use of products which titanium dioxide is
	bound to other materials, such as paints."
	(b) OSHA does not regulate titanium dioxide as a carcinogen. However, under 29CFR 1910.1200 the SDS must convey the
	fact that titanium dioxide is a potential carcinogen to rats. See additional information below.
	Note: Normal application procedures for this product pose no hazard as to the release of respirable titanium dioxide dust,
	but grinding or sanding dried films of this product may yield respirable titanium dioxide. Use appropriate protection.
Reproductive toxicity	No data available.
Specific organ toxicity (single exposure)	No data available
Specific organ toxicity (repeated exposure)	No data available
Aspiration hazard	No data available.
Additional Information	In lifetime inhalation studies rats were exposed for 2 years to Titanium Dioxide Pigment – Dry Grades at 10, 50 and 250 mg/s
	of respirable TiO ₃ . Slight lung fibrosis was observed at 50 and 250 mg/m ³ levels. Microscopic lung tumors were also observed
	in 13 percent of the rats exposed to 250 mg/m³, an exposure level that caused lung overloading and impairment of rat lung's
	clearance mechanisms. In further studies, these tumors were found to occur only under particle overload conditions in a
	uniquely sensitive species, the rat, and have little or no relevance for humans. The pulmonary inflammatory response to TiO,
	particles exposure was also found to be much more severe in rats than in other rodent species.
	In February 2006, IARC re-evaluated Titanium dioxide as pertaining to Group 2B: "possibly carcinogenic to humans", based
	upon inadequate evidence in humans and sufficient evidence in experimental animals for the carcinogenicity of titanium
	dioxide. IARC evaluation guidelines consider the generation of tumors, in 2 different studies within the same animal species,
	be adequate criteria for an assessment of sufficient evidence.
	The conclusions of several epidemiology studies on more than 20000 TiO, industry workers in Europe and the USA did
	not suggest a carcinogenic effect of TiO, dust on the human lung. Mortality from other chronic diseases, including other
	respiratory diseases was also not associated with exposure to TiO, dust.
	Based upon all available study results, DuPont scientists conclude that titanium dioxide will not cause lung cancer or
	chronic respiratory diseases in humans at concentrations experienced in the workplace.

	SECTION 12 ECOLOGICAL INFORMATION	
12.1	Toxicity	No data available
12.2	Persistence & degradability	No data available
12.3	Bioaccumulation potential	No data available
12.4	Mobility in soil	No data available
12.5	Results of PBT & vPvP assessment	Not required. Not conducted.
12.6	Other adverse effects	No data available

Flame Seal Products, Inc. 15200 West Drive, Houston, TX 77053 USA

www.flameseal.com | 713-668-4291 [office] | 713-668-1724 [fax] | **Emergency No. (Chemtrec): 800-424-9300**

SDS v1.0 | Date : 05/29/2015



SECTION 13 DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Product Incinerate or mix with T50 curing agent and allow mixture to solidify, then bury in a suitable land fill where permitted by local

regulations. Or contact a licensed disposal facility.

Contaminated packaging Dispose of a unused product

SECTION 14	TRANSPORT INFORMATION	
DOT (US)	Not dangerous goods	
IMDG	Not dangerous goods	
IATA	Not dangerous goods	

SECTION 15 REGULATORY INFORMATION			
SARA 302 Components	No chemicals in this product are subject to the reporting requirements of SARA Title III, section 302.		
SARA 313 Components	This product does not contain any chemical components with known CAS numbers that exceed the threshold (DeMinimis)		
	reporting levels established by SARA Title III, section 313.		
SARA 311/312	This product does not contain any SARA 311/312 hazards.		
New Jersey, Pennsylvania, Massachusetts	Titanium Dioxide	CAS # 13463-67-7	REV. date 1994-04-01
Right to Know Components			
Clean Water Act	Section 311 lists phosphorous as a hazardous substance, which if discharged into or upon water, will present an imminent		
	and substantial danger to public welfare. Spills of >= 5000 pounds (approx. 50,000 pounds of FSTB) must be reported		pprox. 50,000 pounds of FSTB) must be reported to the
	National Response Center @ 1-800-424-8802.		
California Prop. 65	WARNING! This product contains a chemical known to the state of California to cause cancer in respirable form. Titanium Dioxide.		
WHMIS	D2A – Carcinogen as respirable dust. Titanium Dioxide.		
IARC	Group 2B – Possible human carcinogen – as respirable dust. Titanium Dioxide.		
RTECS #	XR 2275000		

Titanium dioxide included in the Candidate List of Substances of Very High Concern (SVHC) according to Regulation(EC) No. 1907/2006(REACH) - Respirable form.

SECTION 16 OTHER INFORMATION

Full text of H-statements referred to under sections 2 and 3

H316:3 Cause mild skin irritation.
H320: 2B Causes eye irritation.

Hazard pictograms not required per Tables 3.2.5, 3.2.5.1, 3.3.5, 3.3.5.1 of the GHS of Classification and Labeling of Chemicals Fifth Revised Edition.

Hazards by conclusion drawn from relevant literature and documentation from similar products.

HMIS Rating	Health hazard	1
	Chronic health hazard	*
	Flammability	0
	Physical hazard	0
NFPA	Health hazard	1
	Fire hazard	0
	Reactivity hazard	0

Flame Seal Products, Inc. 15200 West Drive, Houston, TX 77053 USA

www.flameseal.com | 713-668-4291 (office) | 713-668-1724 (fax) | **Emergency No. (Chemtrec): 800-424-9300**

SDS v1.0 | Date: 05/29/2015



SECTION 16 OTHER INFO	RMATION			
Full text of H-statements referred to under sections 2 and 3				
H316:3	Cause mild skin irritation.			
H320 : 2B	Causes eye irritation.			
Hazard pictograms not required per Tables 3.2.5, 3.2.5.1, 3.3.5, 3.3.5.1 of the GHS of Classification and Labeling of Chemicals Fifth Revised Edition.				
Hazards by conclusion drawn from relevant literature and documentation from similar products.				
HMIS Rating	Health hazard	1		
	Chronic health hazard	*		
	Flammability	0		
	Physical hazard	0		
NFPA	Health hazard	1		
	Fire hazard	0		
	Reactivity hazard	0		

The information in this document is based on the present state of Flame Seal Products' knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantees to the properties of the product. Flame Seal Products shall not be held liable for any damage from handling or from contact with the above product.

Flame Seal Products, Inc. 15200 West Drive, Houston, TX 77053 USA

www.flameseal.com | 713-668-4291 [office] | 713-668-1724 [fax] | **Emergency No. (Chemtrec): 800-424-9300**

SDS v1.0 | Date : 05/29/2015